

Shinn Thon UK Ltd

1st Floor, 223 Dalton Road, Barrow in Furness, Cumbria. LA14 1PQ
Tel: 0870 609 2264 Fax: 01229 833 733 E-mail: sales@shinnthon.com

Product Datasheet

SH5011

Double Sided Carpet Tape 50mm



Specifications:

Double side cloth tape
Coated with hotmelt adhesive
Brown liner
Length: 25m/10m

Applications

Carpet use
Hole closure, repairing and masking
Interior and exterior use
Packaging, holding and bundling

Technology Data:

Total thickness	Adhesive to steel	Tensile Strength	Rolling ball tack	Elongation	Holding power	Service temperature range
(mm)	(oz/inch)	(N/CM)	(Ball no.)	(N/CM)	(Hours)	(°C)
0.24-0.25	45-55	20-30	> 10	N/A	> 2	-15°C -> +60°C

Usage:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum

Dimensions may differ from those shown

Shinn Thon UK Ltd

1st Floor, 223 Dalton Road, Barrow in Furness, Cumbria. LA14 1PQ
Tel: 0870 609 2264 Fax: 01229 833 733 E-mail: sales@shinnthon.com

of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of 6 months.

Complies to:

RoHS 2011/65/EU

Issue Date: 01/01/2013
Revision: E